

Moore Brothers Oct-29 1913

T 1 N 16 32 5 1/2 m

Chains Links

- Commencing at the $\frac{1}{4}$ sec corner bet No 9 9 10 1/2 m
- 20 00 Set Iron pins to cor
- 40 00 " " Corner to No 3-4-9 9 10
and at
- 60 00 Set Iron pins to cor
- 79 44 The $\frac{1}{4}$ sec corner bet No 3 9 4
then north on true line
- 13 11 Set Stone 16 x 8 x 6 ft to cor
- 26 22 Set Stone 18 x 6 x 7 ft corner to No 3-4-9 9 10
from $\frac{1}{4}$ sec, bet 3 9 10 1/2 m west
- 20 01 Set Iron pins to cor
- 35 68 The corner to No 3-4-9 9 10
west bet No 4 9 9
- 52 52 feet the corner to No 4-5-8 8 9
then east on true line
- 26 26 Set Post for $\frac{1}{4}$ sec corner
corner bet No 8 8 9
- 25 74 Set Iron pins to cor
- 57 79 the corner to No 5-9-16 8 17
then 1/2 m north on true line
- 25 85 Set Stone 18 x 9 x 6 bet $\frac{1}{4}$ sec corner
- 12 94 1/2 Set Stone 16 x 8 x 7 1/2 to cor
West through center No 9
- 26 40 Set Iron pins to cor
- 52 68 The $\frac{1}{4}$ sec corner
then 1/2 m east on true line
- 26 84 Set Stone for center No 9

Chain

Links

- 52 68 The $\frac{1}{4}$ Sec corner bet No 9 & 10
North through center $N \frac{1}{2}$ No. 9
- 13 20 set $\frac{1}{2}$ pole $\frac{1}{6}$ cor
- 26 20 The $\frac{1}{4}$ pole cor bet No 4 & 9
these south on same line
- 13 10 set post for $\frac{1}{6}$ cor Center $N \frac{1}{2}$ No. 9
North through center $S \frac{1}{2}$ No. 4
- 26 35 the center No. 4
these south on same line
- 13 17 $\frac{1}{2}$ set post for center $S \frac{1}{2}$ No. 9
From the center $W \frac{1}{2}$ cor
North through center $N \frac{1}{2}$ No. 10
- 26 24 the $\frac{1}{6}$ cor
these $\frac{1}{6}$ cor south on same line
- 13 12 set stone for $\frac{1}{6}$ cor
North through center $S W \frac{1}{4}$ No. 3
- 26 50 a point 9 feet east of $\frac{1}{6}$ cor
these south on same line
- 13 25 set stone 16 + 4 + 6 ft $\frac{1}{6}$ cor in center $S W \frac{1}{4}$ No. 3
- 26 50 the $\frac{1}{6}$ cor on State boundary $S W \frac{1}{4}$ No. 3
Seoy Winbree County Surveyor
by John W. Winbree Deputy
assisted by Jack and O. H. Marks